



(*) VALUE FOR TYRES 10.0/75X15.3
 (**) VALUE IN DEPEND OF EQUIPMENT AND TYRES

BASIC TECHNICAL PARAMETERS	
TYPE OF DRAWBAR SUSPENSION	UNSPRUNG
TYPE OF AXLE(S) SUSPENSION	UNSPRUNG
TRACK [mm]	2100
WHEEL BASE [mm]	-
MAX. ALLOWED SPEED [km/h]	25
OIL REQUIREMENTS [l]	-
TYRES AND DISCS	ACCORDING TO CHART
CONNECT DIMENSION OF DISC [mm]	∅220/∅275
NUMBERS/ DIMENSIONS WHEEL SCREWS	8/M18x1.5
TYPE OF CONNECTION DEVICE	TOWING EYE ∅40
BASIC OUTSIDE DIMENSIONS	
LENGTH [mm]	4065
WIDTH [mm]	2550
HEIGHT [mm]: BASIC (*)	2253
WITH EXTENSION (*)	-
HEIGHT OF CONNECT DEVICE ABOVE GROUND [mm] (*)	478
DIMENSIONS AND PARAMETERS OF BODY FLOOR	
LENGTH [mm]	-
WIDTH [mm]	-
BASIC HEIGHT OF SIDES [mm]	-
HEIGHT OF EXTENSION [mm]	-
BODY VOLUME [m³]: BASIC	4,5
WITH EXTENSION	-
PLATE THICKNESS FLOOR/ SIDES [mm]	3
TIPP ANGLE TO BACK/ TO SIDE [°]	-
HEIGHT DURING TIPPING [mm]: TO BACK (WITHOUT/ WITH EXTENSION) (*)	-
TO SIDE (WITHOUT/ WITH EXTENSION) (*)	-
WEIGHTS	
SERVICE (WITH/ WITHOUT EXT.) [kg] (**)	1300/-
PAYLOAD (WITH/ WITHOUT EXT.) [kg] (**)	4700/-
HIGHEST ALLOWED/ TECHNICAL PERMISSIBLE [kg]	6000
MAX. DRAWBAR LOAD [kg]	1000

ALTERNATIVES OF USED TYRES

TYRE	DISC	TYRE DIAMETER [mm]	TYRE WIDTH [mm]
14.5/80-18	11x18	104,5	372

DRAWN: ING. HALAMA CONTROLLED: ING. PIKULA

DATE: 15.3.2018

PRODUCT:

WATER TANK

TYPE NAME: **RTV4,5**

DATE: 15.3.2018

PRODUCT:

WATER TANK

COMMERCIAL NAME: **RTV4,5**

